

PRODUCT DATA SHEET

#23-00

LUSTERLITE GLOSS ENAMEL

DESCRIPTION

LUSTERLITE GLOSS ENAMEL is a synthetic-Alkyd oil based gloss enamel. This product is for rust preventive coating on the metal substrate.

USE

Residential or commercial applications.
Exterior/Interior. Sash and trim, metal, wood, equipment and other properly primed and prepared surfaces.

COLOR

White, black, and five tinting bases. Various range of custom colors are available upon request.

FINISH: Gloss. (85% up @60 gloss meter)

COVERAGE: 400 to 450 sq. ft. per gallon.

Actual coverage may vary due to surface conditions and applying technique.

THINNING: Use at package consistency.

DRYING TIME: Dry to touch 4 hours. Recoat in approximately 24 hours. Actual drying time may vary depending on temperature and humidity.

SURFACE PREPARATION

New work: All surfaces must be clean, dry and free of dust, rust, dirt, stains, mildew, grease, wax, oil, efflorescence or other foreign materials that could cause adhesion problems.

Allow concrete or stucco to cure before application of primer and finish coats.

Pre treat all galvanized, non ferrous metal, newly poured or pre casted concrete surfaces. Patch all voids, cracks, and holes with appropriate patching or caulking materials. New surfaces should be sealed with suitable primer/sealer.



SINCE 1936

Old Works: Remove any loose or peeling paints. The imperfect surfaces must be filled with suitable patching compound and sanded. Bare or repaired surfaces should be primed with suitable primer for the substrate involved. Glossy surfaces should be dulled down to provide a “tooth” for adhesion by either sanding or chemical method.

Warning– Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

APPLICATION: Brush, roll or spray

CLEAN-UP: Use mineral spirits or paint thinner.

PRIMER

Drywall/Plaster:

8600 - PVA Sealer

8100 - ACRYLIC LATEX UNDERCOATER

Stucco/Concrete:

7100 - EVERBOND CONCRETE PRIMER

7200 – ACRA-POXY PRIMER

Wood: 7700 - TOTAL-PREP

Ferrous metal:

7400 - ALKYD METAL PRIMER

8300 - ACRA METAL PRIMER

Non ferrous metal: 8300 - ACRA METAL PRIMER

VOC: Does not exceed 400 grams per liter.

MATERIAL SAFETY DATA SHEET

Available at www.tibbettspaint.com