

PRODUCT DATA SHEET

#3800

FASTLANE TRAFFIC PAINT



DESCRIPTION

FASTLANE is a fast drying 100% Acrylic Traffic Paint designed for marking traffic lanes on asphalt, concrete and parking lots. FASTLANE offers excellent adhesion, chemical resistance, color retention and high washability.

USE

Asphalt or concrete and primed wood and metal surfaces. Highways, parking lots, curbs, medians.

COLOR

Four colors - (White, Red, Yellow and Blue)

FINISH: White, Yellow, Blue - Flat finish
Red - Satin Finish

Viscosity@77 F: 100-105 KU
Weight per gallon: 12.9 Lbs/Gal
Solid by Volume: 40.5 \pm 2%
Solid by Weight: 56.4 \pm 2%
Recommended film thickness per coat:
Wet: 5.0 mils Dry: 2.0 mils

COVERAGE

Spreading rate at 4" stripe results approximately 500 lineal feet. The actual coverage may vary depending on surface conditions, film thickness and application technique.

THINNING: This product is formulated to be used at package consistency. However, if thinning is required, add water sparingly for good flow and workability.

DRYING TIME: Dry to touch in 30 minutes depending on film thickness, humidity and time of day being applied.

SURFACE PREPARATION

All surfaces must be clean, dry and free of dust, rust, dirt, oil, grease, and rust, stains, or other contaminants. Asphalt seal coats should be allowed to dry at least 48 hours before applying FASTLANE. When applied this product, it will dry to no pick-up in 30 minutes at 70 - 80 degrees F. Repair all holes, cracks, etc. with a good grade asphalt patch or concrete patch.

Warning- Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

APPLICATION

Brush, roller, conventional airless spray and most any line marking machines.

VOC: Less than 100 grams per liter

CLEAN-UP: Clean tools, equipment and area with soap and warm water.

MATERIAL SAFETY DATA SHEET

Available at www.tibbettpaint.com