

PRODUCT DATA SHEET

#57-00

TITAN POLY-URETHANE GLOSS

DESCRIPTION

Synthetic-alkyd based, TITAN POLY-URETHANE GLOSS is clear and can be used for all kinds of Interior Wood surfaces.

USE

Interior: Furniture, cabinets, wood paneling, doors, railings.

COLOR: Clear

FINISH: Gloss. (85% @60 gloss meter)

COVERAGE: 400 to 500sq. ft. per gallon.

Actual coverage may vary due to surface conditions and applying technique.

THINNING: Use at package consistency.

DRYING TIME: Dries in 12 - 18 hours. Allow to dry at least 16 hours before recoating. Actual drying time may vary depending on temperature, humidity, and film thickness.

SURFACE PREPARATION

New Works: All surfaces should be clean, dry and free of dust, dirt, oil wax or other foreign matters. Surface imperfections such as nail holes, roads and cracks should be patched and filled with suitable patching compound to blend with surrounding surfaces. Patched and filled surfaces should be sanded with fine grit sand paper, and cleaned with tack rag to remove dust, lint and grit.



SINCE 1936

Old Works: All surfaces should be cleaned to remove dirt, grease, oil and wax. For previously varnished surface, sand with fine sand paper and clean with tack rag to remove any foreign matters

Warning– Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

PRIMER

On bare wood, apply varnish sanding sealer before this product.

APPLICATION

Do not Shake. Stir thoroughly before use. Do not make thick coats or it may wrinkle. Do not use over shellac or lacquer. All finishes affect wood color. Test sample on small hidden area to see the final effect before doing a complete job. Brush. Sand lightly between each coats for adhesion and smoothness.

CLEAN-UP: Use mineral spirits or paint thinner.

VOC: Does not exceed 275 grams per liter.

MATERIAL SAFETY DATA SHEET

Available at www.tibbettspaint.com