

PRODUCT DATA SHEET

#7500

KWIK-SAND

100% ACRYLIC PRIMER UNDERCOAT

DESCRIPTION

KWIK-SAND provides a foundation for water or solvent-based finish coats. Due to its superior adhesion, KWIK-SAND can be used as bond coat even on the alkyd glossy surface.

(**NOT** recommended for priming exterior bare woods.)

USE

Residential or commercial use.

Interior/Exterior. Wood, concrete, drywall, plaster, masonry, aluminum, and galvanized metal, except the area patched with drywall mud, or sparkling paste – it cause mud cracked.

COLOR: White

FINISH: Flat

Viscosity@77 F: 95-105 KU

Weight per gallon: 10.5 Lbs/Gal

Solid by Volume: 37.0 \pm 2%

Solid by Weight: 48.2 \pm 2%

Recommended film thickness per coat:

Wet: 4.5 mils Dry: 1.5 mils

COVERAGE: 300 to 350 sq. ft. per gallon.

Actual coverage may vary due to surface conditions and applying technique.

THINNING: This product is formulated to be used at package consistency. However, if thinning is required, add water sparingly for good flow and workability.

DRYING TIME: Dry to touch in 2 hours. Recoat in 4 hour.

Actual drying time may vary due to temperature and humidity.



SURFACE PREPARATION

All surfaces must be clean, dry and free of dust, rust, dirt, stains, mildew, grease, wax, oil, efflorescence or other foreign materials that could cause adhesion problems. Peeling, cracked and crazed paint should be sanded smooth to a sound surface. All cracks are patched and sanded with proper patching materials. Rusted surface should be wire brushed; mildewed surfaces should be washed with mildew remover, followed by water rinse and be allowed to dry.

Although **KWIK-SAND** can be used on glossy surfaces, it is always advantageous to sand the glossy surface prior to the application of the primer.

Warning– Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

APPLICATION

Brush, roll or spray. Do not apply this product when surface or air temperature is below 50 degrees Fahrenheit. Protect all surrounding areas from splash, over-spray and spill during application.

VOC: Less than 100 grams per liter

CLEAN-UP: Clean tools, equipment and area with soap and warm water.

MATERIAL SAFETY DATA SHEET

Available at www.tibbettpaint.com