

PRODUCT DATA SHEET

#7700

TOTAL PREP

DESCRIPTION

TOTAL PREP is a premium quality stain blocking water-based primer/sealer. **TOTAL PREP** is particularly effective in blocking tannin stain on redwood and cedar. **TOTAL PREP** is also a rust-inhibitive primer and will provide mildew resistant coating for exterior and interior surfaces.

USE

Residential or commercial use.

Exterior/Interior. Wood, stucco, concrete, concrete tilt-up, masonry, and plaster.

COLOR: White

FINISH: Flat

Viscosity@77 F: 95-105 KU

Weight per gallon: 10.5 Lbs/Gal

Solid by Volume: 37.0 \pm 2%

Solid by Weight: 48.2 \pm 2%

Recommended film thickness per coat:

Wet: 4.5 mils Dry: 1.5 mils

COVERAGE: 300 to 350 sq. ft. per gallon.

Actual coverage may vary due to surface conditions and applying technique.

THINNING: This product is formulated to be used at package consistency. However, if thinning is required, add water sparingly for good flow and workability.

DRYING TIME: Dry to touch in 2 hours. Recoat in 4 hour. Actual drying time may vary due to temperature and humidity.

SURFACE PREPARATION

All surfaces must be clean, dry and free of dust, rust, dirt, stains, mildew, grease, wax, oil, efflorescence or other foreign materials that could cause adhesion problems. Peeling, cracked and crazed paint should be sanded smooth to a sound surface. All cracks are patched and sanded with proper patching materials. Rusty surface should be wire brushed; mildewed surfaces should be washed with mildew remover, followed by water rinse and be allowed to dry.



Although **TOTAL PREP** can be used on glossy surfaces, it is always advantageous to sand the glossy surface prior to the application of the primer.

Special Recommendations:

For maximum stain blocking, apply one coat of **TOTAL PREP** and cure 4 hours; and apply a second coat of **TOTAL PREP** and allow to cure over 16 hours before top coating.

1)WOOD SURFACE: TOTAL PREP is an excellent undercoater for both exterior and interior uses. For maximum tanning stain on redwood, cedar and knots, use two coats of **TOTAL PREP**.

2) WATER STAINS (Interior): One or two coats of **TOTAL PREP** will block most medium water stains. For heavy water stains, **#88 BLOCK-OUT** (solvent-based) is preferred.

3) SPOT PRIMING: Spot priming on some surfaces may result in a non-uniform appearance of final coat. To avoid this occurrence, prime the entire surface, rather than spot prime.

Warning– Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

APPLICATION

Brush, roll or spray. Do not apply this product when surface or air temperature is below 50 degrees Fahrenheit. Protect all surrounding areas from splash, over-spray and spill during application.

VOC: Less than 100 grams per liter

CLEAN-UP: Clean tools, equipment and area with soap and warm water.

MATERIAL SAFETY DATA SHEET

Available at www.tibbetbspaint.com