

PRODUCT DATA SHEET

#8600

PVA HI-HIDE SEALER

DESCRIPTION

Vinyl acrylic based, PVA HI-HIDE SEALER, is a pigmented wall sealer designed to provide a smooth surface for finish coats by reducing suction, bridging hair line cracks and filling pores of the substrate involved.

USE

Residential or commercial use.

Interior. Wide range of surfaces such as wood, plaster, gypsum drywall, masonry, particle board and previously painted surfaces.

COLOR: White

FINISH: Flat

Viscosity@77 F: 95-105 KU

Weight per gallon: 10.1 Lbs/Gal

Solid by Volume: 30.0 \pm 0.5%

Solid by Weight: 41.0 \pm 0.5%

Recommended film thickness per coat:

Wet: 4.0 mils Dry: 1.2 mils

COVERAGE: 300 to 350 sq. ft. per gallon.

Actual coverage may vary due to surface conditions and applying technique.

THINNING: This product is formulated to be used at package consistency. However, if thinning is required, add water sparingly for good flow and workability.

DRYING TIME: Dry to touch in 2 hours. Recoat in 4 hour. Actual drying time may vary due to temperature and humidity.

SURFACE PREPARATION

New work: All surfaces must be clean, dry and free of dust, rust, dirt, stains, mildew, grease, wax, oil, efflorescence or other foreign materials that could cause adhesion problems.



SINCE 1936

Allow concrete or stucco to cure before application of primer and finish coats.

Pre treat all galvanized, non ferrous metal, newly poured or pre casted concrete surfaces. Patch all voids, cracks, and holes with appropriate patching or caulking materials. New surfaces should be sealed with suitable primer/sealer.

Old work: Power wash, scrape, sand and completely clean to remove any dirt, rust, chalk, grease, oil, wax, loose paint or any other foreign materials. Glossy surfaces should be dulled down for good adhesion.

Warning– Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

APPLICATION

Brush, roll or spray. Do not apply this product when surface or air temperature is below 50 degrees Fahrenheit. Protect all surrounding areas from splash, over-spray and spill during application.

VOC: Less than 50 grams per liter

CLEAN-UP: Clean tools, equipment and area with soap and warm water.

MATERIAL SAFETY DATA SHEET

Available at www.tibbetbspaint.com