

# PRODUCT INFORMATION

## #88-00 BLOX-OUT PRIMER

<b>DESCRIPTION</b>	Alkyd-based, BLOX-OUT is a premium interior stain blocking primer with excellent sealing qualities. This product will provide a smooth surface foundation for latex and alkyd finish coats.
<b>COLOR</b>	White.
<b>FINISH</b>	Flat.
<b>USE</b>	Interior. Wood, masonry, kitchens, cabinets, drywall, and well cured plaster. May be used as an intermediate coat over previously enameled surfaces.
<b>SURFACE PREPARATION</b>	<p><u>New Works:</u> All surfaces must be clean, dry and free of dust, rust, dirt, stains, mildew, grease, wax, oil, efflorescence or other foreign materials that could cause adhesion problems. Allow concrete, stucco, drywall or plaster to cure before application of primer and finish coats. Pretreat all galvanized, non-ferrous metal, newly poured and precast concrete surfaces. Patch all voids, cracks, and holes with appropriate patching or caulking materials. New surfaces should be sealed with suitable primer/sealer.</p> <p><u>Old Works:</u> Previously painted surfaces should be thoroughly cleaned to avoid adhesion problem. Imperfect surfaces should be patched and sanded to match the surrounding surface. Glossy surfaces should be downed either by sanding or chemical method. All construction defects that might permit water to get behind the paint film should be repaired.</p>
<b>APPLICATION</b>	Brush, roller, or spray.
<b>THINNING</b>	Not recommended.
<b>COVERAGE</b>	Approximately 350-450 sq. ft per gallon. The actual coverage may vary depending on surface conditions and application technique.
<b>DRYING TIME</b>	Dry to touch 1 - 2 hours. Recoat in approximately 24 hours. The actual drying time may vary depending on temperature and humidity.
<b>CLEAN-UP</b>	Use mineral spirits or paint thinner.
<b>V.O.C.</b>	Does not exceed 350 grams per liter.

