

PRODUCT DATA SHEET

#9200

CONCRETE GLUE ACRYLIC

DESCRIPTION

CONCRETE GLUE ACRYLIC is formulated with a highly water resistant and alkali resistant acrylic resin. This is designed as a bonding agent to improve the adhesion of new concrete, cement and mortar to any sound surfaces. Also this can be mixed directly into the cementitious material as part of the liquid addition.

USE

Polymer admixture for cement-based products.
Primer over cementitious substrates.

BENEFITS

Improves flow of cement based systems
Improves flexural strength and modulus of elasticity.
Reduces permeability of cement matrices.
Provides extra bond strength in wet and dry.
High alkali stability

COLOR: Milky white

Viscosity@77 F: 65 - 75 KU
Weight per gallon: 8.62 Lbs/Gal
Solid by Volume: 32.4 \pm 0.5%
Solid by Weight: 34.3 \pm 0.5%

MIXING INSTRUCTION

Use the recommended amount of **#9200 CONCRETE GLUE ACRYLIC** along with sufficient water to provide proper consistency.

Stucco Patch 90 lb bag may require 1.5 gallons of #9200.

Mortar Mix 40 lb bag may need half a gallon of #9200.

If it is used as a bonding agent, do not thin with water.

CLEAN-UP: Clean tools, equipment and area with soap and warm water.



SINCE 1936

SURFACE PREPARATION

New work: All surfaces must be clean, dry and free of dust, rust, dirt, stains, mildew, grease, wax, oil, efflorescence or other foreign materials that could cause adhesion problems. Allow concrete or stucco to cure before application of primer and finish coats. Pre treat all galvanized, non ferrous metal, newly poured or pre casted concrete surfaces. Patch all voids, cracks, and holes with appropriate patching or caulking materials.

Old work: Power wash, scrape, sand and completely clean to remove any dirt, rust, chalk, grease, oil, wax, loose paint or any other foreign materials. Glossy surfaces should be dulled down for good adhesion.

Warning– Special instructions

If you scrape, sand, or remove old paint of old buildings (especially pre 1978), you may release lead dust or asbestos dust. Exposure to lead dust and asbestos dust can cause serious illness, such as brain damage, lung cancer. Always wear proper personal protective equipment during surface preparation, and Finish cleanup of any residues. For more information, log on to www.epa.gov/lead or www.epa.gov/asbestos. Or contact at 1-800-424-LEAD.

VOC: Less than 30 grams per liter

WARNING

Do not apply if temperature is below 50 degree F.

Do not use on areas exposed to submersion in water such as swimming pools.

Keep out of reach of children. Do not take internally.

Keep from freezing. Close container after each use.

MATERIAL SAFETY DATA SHEET

Available at www.tibbettpaint.com